

39/50 DCSS High-Performance In-Tank Fuel Pump

Model No. F90000262

Product Highlights

- Designed for engines with more than 500 HP
- Award-winning OE technology
- High-pressure, high-flow performance
- Requires modifications to wiring, fuel lines and fuel module
 - Professional installation recommended
- Outperforms all current market in-tank fuel pumps



12.0 Volts

Pressure (psi)	Averages		
	Flow (lph)	Current (amps)	Speed rpm
0	404.92	11.33	4741
10	402.69	11.29	4787
20	402.85	11.31	4907
30	382.33	11.83	4907
40	351.97	12.57	4715
50	320.38	13.32	5834
60	287.86	14.09	6395
70	256.83	14.92	5671
80	223.73	15.75	5328
90	189.63	16.64	4632
100	97.29	17.45	3696
110	32.08	18.34	3100
120	2.44	18.57	3018
Shutoff	2.43	18.71	3010

13.5 Volts

Pressure (psi)	Averages		
	Flow (lph)	Current (amps)	Speed rpm
0	440.35	13.08	5228
10	439.86	13.12	5362
20	441.72	13.17	5571
30	432.30	13.38	5785
40	404.59	14.12	5353
50	377.65	14.88	5421
60	346.57	15.64	4833
70	316.23	16.45	4748
80	285.38	17.25	5852
90	252.68	18.07	4654
100	155.28	18.78	4035
110	96.34	19.68	3776
120	17.20	20.24	3556
Shutoff	2.53	20.19	3614

Flow vs. Pressure

